

LSI ABOLITE LIGHTING RLM ANGLED REFLECTOR



Combining a nostalgic look with today's lamp sources for effective signage illumination.




LSI ABOLITE LIGHTING RLM ANGLED REFLECTOR

CAST THE PERFECT HIGHLIGHT ON SIGNS, PRODUCT DISPLAYS, AND KEY ARCHITECTURAL FEATURES

Effective signage illumination is the primary objective of the LSI Abolite Angled Reflector (AD). While definitely a nostalgic luminaire, combining it with today's lamp sources provides the lighting designer with a major tool for addressing both illumination levels and energy requirements. By mounting the AD in combination with the A-style gooseneck on four foot centers, both interior and exterior signage can be illuminated with confidence.

- **Compact profile** with 3/4" threaded entry
- **Mounting** accomplished with rigid 3/4" conduit, or a variety of brackets and goosenecks
- **Three sizes** ranging from 7" to 11" in diameter make the AD a great choice when directional lighting is needed
- **Lamps available**
 - Compact Fluorescent, Pulse Start Metal Halide, Metal Halide and Incandescent
- **Finishes offered** include metallic silver, gloss white, gloss black, gloss red, textured graphite, textured rust, satin verde green, satin copper and satin turquoise

See data sheet for complete specifications – www.lsi-industries.com



U.L. Listed for wet locations.

Also available in LED

Fixture	Height (A)	Width (B)	Neck (C)	Weight (lbs./kg)
AD 100	10" (254mm)	7" (178mm)	5" (127mm)	2.0 lbs. / .9kg
AD 150	11-1/2" (292mm)	9" (229mm)	5-1/4" (133mm)	2.0 lbs. / 1.1kg
AD 200	13-1/2" (343mm)	11" (279mm)	5-1/2" (140mm)	2.5 lbs. / 1.1kg



LSI LIGHTING SOLUTIONS PLUS

10000 Alliance Road ♦ Cincinnati, Ohio 45242 ♦ (513)793-3200 ♦ FAX (513)793-0147 ♦ www.lsi-industries.com